

FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD-T3510

Telehandler



Representative product image. Attachments shown may be optional.

3,500 kg

RATED LOAD

10.5 m

MAXIMUM LIFT HEIGHT

77.3 kW

RATED ENGINE POWER

KD-T3510 telehandler with a 3,500 kg rated load, 10.5 m maximum lift height and 77.3 kW engine. 3-section telescopic boom, four-wheel drive and front-wheel, four-wheel and crab steering.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 TECHNICAL SUPPORT

KD-T3510 / Telehandler**LOAD & LIFT**

Rated load	3,500 kg
Maximum lift height	10.5 m
Telescopic boom sections	3
Fork length and type	1,220 mm sliding forks

ENGINE & CONTROLS

Engine - configuration shown	Yuchai
Rated engine power	77.3 kW
Hydraulic control	Load-sensing electro-proportional multiway valve system

CHASSIS & CONFIGURATION

Drive	Four-wheel drive
Steering modes	Front-wheel / four-wheel / crab
Transmission	High/low-range transmission, 4 forward / 4 reverse gears
Tire size	405/70-20
Quick coupler	Hydraulic
Frame material	355 manganese-steel plate
Boom material	BS1000 steel
Single-axle load rating (supplier figure)	10,000 kg

Standard configuration

- LED work lights
- Window-breaking hammer
- Fire extinguisher
- Rear sliding window
- 10-inch driving/reversing camera display
- Electronically controlled travel
- Automatic fork levelling
- Four-wheel drive
- Front-wheel, four-wheel and crab steering modes
- Plate-fin radiator
- Fore-aft adjustable steering column with large instrument housing
- Adjustable deluxe operator seat
- Protected Xiangliu hydraulic hoses
- Frame made from 355 manganese-steel plate
- BS1000 steel telescopic boom
- 1,220 mm sliding forks
- Deluxe cab
- Colour LCD display
- Multimedia system
- Rear and front-right cameras
- Air-braked axles
- Load-moment limiting system
- Heating and cooling air conditioning
- Stabilizer legs
- Cast-iron counterweight

Available options

- Engine alternatives: China II - Cummins 4BT3.9-C100 75 kW; Euro III (exact non-road stage not confirmed) - Yanmar 63 kW, Cummins QSB3.9-C100; EU Stage V - Perkins 74.5 kW, Yuchai 74 kW, YUNNEI 74 kW, Fiat 75 kW; EPA4 / US EPA Tier 4 - Perkins 74.5 kW, Cummins QSF3.8, Fiat 75 kW. Options are supplier-listed alternatives. Exact engine, emissions documentation, compatibility and final configuration require order confirmation.
- Domestic closed-loop hydrostatic system (travel pump, piston pump and travel motor)
- Danfoss closed-loop hydrostatic system (travel pump, piston pump and travel motor)
- Zhuoshibo wet-brake axles, including braking system
- Solid tires
- Diesel cab heater

Rated load and maximum lift height are separate specifications. Request the model-specific load chart for permitted loads at each height and reach. Images and shared series video may show optional attachments or a different configuration.

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations are available subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.