

FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD20-15

Backhoe Loader



Representative product image. Attachments shown may be optional.

1,500 kg

RATED LOAD

55 kW

RATED ENGINE POWER

2.5 m

MAXIMUM DIGGING DEPTH

KD20-15 backhoe loader with a 1,500 kg rated loading capacity, 55 kW engine and 2,500 mm maximum digging depth.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 TECHNICAL SUPPORT

KD20-15 / Backhoe Loader**LOADER**

Rated load	1,500 kg
Maximum dumping height - loader	3,500 mm
Minimum rotary radius - loader	900 mm
Maximum dumping distance	900 mm
Boom lifting time	4.5 s
Boom lowering time	3 s
Total cycle time	10 s
Maximum breakout force - loader	20 kN

BACKHOE

Maximum digging depth	2,500 mm
Maximum digging height	3,500 mm
Maximum digging radius	4,500 mm
Maximum dumping height - backhoe	2,500 mm
Backhoe bucket capacity	0.2 m ³
Working efficiency - supplier figure	20-40 m ³ /h
Working cycles - supplier figure	3-5 cycles/min
Maximum hauling force	23 kN
Maximum boom swing angle	180°

ENGINE AND HYDRAULICS

Engine - configuration shown	YUNNEI
Rated engine power	55 kW
Rated engine speed	2,200 rpm
Working pressure	20 MPa
Pump displacement - supplier figure	25 mL/rev

DIMENSIONS AND TRAVEL

Machine weight	4,800 kg
Gradeability	25%

Working speed	<20 km/h
Wheelbase	1,725 mm
Minimum ground clearance	230 mm
Overall dimensions (L × W × H)	7,600 × 2,000 × 2,700 mm

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations are available subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.