FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD30-25A

Backhoe Loader

Representative product image. Attachments shown may be optional.

1,800 kg	85 kW	4.08 m
RATED LOAD	RATED ENGINE POWER	MAXIMUM DIGGING DEPTH

KD30-25A backhoe loader with a 1,800 kg rated loading capacity, 85 kW engine and 4,080 mm maximum digging depth.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 TECHNICAL SUPPORT

QINGDAO KONO DEERE MACHINERY CO.,LTD

info@kono-deere.com | WhatsApp +86 186 6143 3121

KD30-25A / Backhoe Loader

LOADER

Rated load	**1,800 kg**
Loader bucket capacity	**1.0 m³**
Bucket dumping height	**2,795 mm**
Bucket dumping distance	**1,048 mm**
Loading lifting force	**25 kN**
Bucket lifting time	**6.8 s**
Bucket lowering time	**2.5 s**
Bucket discharge time	**1.2 s**
Maximum tractive force	**39 kN**
Maximum breakout force	**38 kN**

BACKHOE

Backhoe bucket capacity	**0.3 m³**
Backhoe dumping height	**3,878 mm**
Maximum digging depth	**4,080 mm**
Maximum digging radius	**5,688 mm**
Bucket swing angle	**180°**
Bucket digging force	**46 kN**
Arm digging force	**31 kN**

ENGINE AND HYDRAULICS

Engine - configuration shown	**Yuchai**
Rated engine power	**85 kW**
System pressure	**20 MPa**
System flow	**120 L/min**

DIMENSIONS AND TRAVEL

Overall dimensions (L × W × H)	**5,900 × 2,300 × 2,850 mm**
Wheelbase	**2,250 mm**
Wheel track	**1,640 mm**

Minimum ground clearance	**300 mm**
Machine weight	**7,600 kg**
Maximum travel speed	**22 km/h**
Minimum turning radius	**5,018 mm**
Tire size	**16/70-20**
Gradeability	**30°**

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations are available subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.