

FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD30-25B

Backhoe Loader



Representative product image. Attachments shown may be optional.

3,000 kg

RATED LOAD

100 HP

RATED ENGINE POWER

4.345 m

MAXIMUM DIGGING DEPTH

KD30-25B backhoe loader with a 3,000 kg rated loading capacity, 100 HP engine and 4,345 mm maximum digging depth.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 TECHNICAL SUPPORT

KD30-25B / Backhoe Loader**LOADER**

Rated front bucket load	3,000 kg
Front bucket capacity	1.0 m ³
Dumping height	2,660 mm
Dumping distance	780 mm
Total cycle time	≤8.8 s
Maximum bucket breakout force	53.3 kN

BACKHOE

Backhoe bucket capacity	0.25 m ³
Maximum dumping height	3,545 mm
Maximum digging depth	4,345 mm
Maximum digging radius	5,385 mm
Maximum arm breakout force	29.6 kN

ENGINE AND TRANSMISSION

Engine alternatives - supplier configuration	YUNNEI / Cummins (optional)
Rated engine power	100 HP
Rated engine speed	2,200 rpm
Supplier emissions label	China III
Maximum engine torque	390 N·m
Drive	Four-wheel drive
Gearbox source figure - input speed / ratio	2,200 rpm / 5.603
Torque conversion ratio	2.64
Gearbox cooling	Air cooling
Front axle transmission ratio	14.77
Rear axle transmission ratio	16.15
Service brake	Wet brake
Brake operation	Mechanical

DIMENSIONS AND TRAVEL

Overall dimensions (L × W × H)	5,900 × 2,320 × 3,500 mm
Curb weight	8,180 kg
Maximum travel speed	36 km/h
Towing force	58 kN
Front wheel track	1,880 mm
Rear wheel track	1,730 mm
Wheelbase	2,170 mm
Turning radius	3,950 mm
Gradeability	17°
Front tire size	20.5-16
Rear tire size	1670-24

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations are available subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.