

FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD30

Wheel Loader



Representative product image. Attachments shown may be optional.

3,000 kg

RATED LOAD

92 kW

RATED ENGINE POWER

2.5 m³

BUCKET CAPACITY

KD30 — Wheel Loader. 3,000 kg · 92 kW · 2.5 m³.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 TECHNICAL SUPPORT

KD30 / Wheel Loader**LOAD & PERFORMANCE**

Rated load	3,000 kg
Bucket capacity	2.5 m ³
Maximum dumping height	2,993 mm
Operating weight	9,700 kg
Maximum dump reach	1,007 mm
Maximum breakout force	127 kN
Maximum traction force	97 kN

ENGINE & HYDRAULICS

Engine - configuration shown	Deutz (Weichai) WP6G125E22
Rated engine power	92 kW
Maximum engine torque	515 N·m
Fuel tank capacity	137 L
Hydraulic tank capacity	90 L
Hydraulic system pressure	16.5 MPa

CHASSIS & DIMENSIONS

Steering angle	36°
Wheelbase	2,630 mm
Tire size	17.5-25
Gradeability	48%
Minimum turning radius (outside tires)	5,097 mm
Minimum turning radius (outside bucket)	5,901 mm
Overall dimensions (L × W × H)	6,890 × 2,440 × 2,080 mm

CYCLE TIMES

Lifting time	4.83 s
Discharge time	1.07 s
Lowering time	3.25 s
Total cycle time	9.15 s

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations are available subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.