

FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD4200A

Sugarcane Loader

THREE-WHEEL SUGARCANE LOADER



KD4200A PRODUCT BRANDING PREVIEW

600 kg

RATED LOAD

76 kW

RATED ENGINE POWER

4.75 m

MAX. GRAPPLE HEIGHT

KD4200A three-wheel sugarcane loader with a 600 kg rated load and a 76 kW YUNNEI engine. The supplied specification lists a 4,200 mm maximum dumping height, a 4,750 mm maximum grapple height and 4,800 kg operating weight.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 AFTER-SALES TECHNICAL SUPPORT

KD4200A

Configuration from the manufacturer-supplied specification. Final order confirmation applies.

GRAPPLE & REACH

Rated load	600 kg
Maximum dumping height	4,200 mm
Maximum grapple height	4,750 mm
Maximum grab size	1,200 mm

ENGINE & POWER

Engine - configuration shown	YUNNEI
Rated engine power	76 kW
Maximum travel speed	20 km/h

DIMENSIONS & WEIGHT

Operating weight	4,800 kg
Overall dimensions (L × W × H)	5,800 × 2,550 × 2,850 mm
Minimum ground clearance	550 mm

CHASSIS & TIRES

Minimum turning radius	3,300 mm
Tire spacing	2,150 mm
Wheelbase	3,300 mm
Front tire size	18.4-30
Rear tire size	400/60-15.5

Optional attachment: Replacement grapple specially designed for palm fruit; confirm in the final order.

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations, subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.