

FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD4200B

Sugarcane Loader

THREE-WHEEL SUGARCANE LOADER



KD4200B PRODUCT BRANDING PREVIEW

800 kg

RATED LOAD

130 HP

RATED ENGINE POWER

5.5 m

MAX. GRAPPLE HEIGHT

KD4200B three-wheel sugarcane loader with an 800 kg rated load and a 130 HP Cummins engine. The supplied specification lists a 4,500 mm maximum dumping height, a 5,500 mm maximum grapple height and 5,000 kg operating weight.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 AFTER-SALES TECHNICAL SUPPORT

KD4200B

Configuration from the manufacturer-supplied specification. Final order confirmation applies.

GRAPPLE & REACH

Rated load	800 kg
Maximum dumping height	4,500 mm
Maximum grapple height	5,500 mm
Maximum grab size	1,200 mm

ENGINE & POWER

Engine - configuration shown	Cummins
Rated engine power	130 HP
Maximum travel speed	20 km/h

DIMENSIONS & WEIGHT

Operating weight	5,000 kg
Overall dimensions (L × W × H)	6,300 × 2,850 × 2,850 mm
Minimum ground clearance	550 mm

CHASSIS & TIRES

Minimum turning radius	3,300 mm
Tire spacing	2,150 mm
Wheelbase	3,300 mm
Front tire size	18.4-30
Rear tire size	400/60-15.5

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations, subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.