FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD4200C

Sugarcane Loader

TELESCOPIC BOOM / ROTATING GRAPPLE

KD4200C PRODUCT BRANDING PREVIEW

800 kg	130 HP	1,000 mm
RATED LOAD	RATED ENGINE POWER	BOOM EXTENSION

KD4200C sugarcane loader with a telescopic boom and rotating grapple. The supplied configuration lists an 800 kg rated load, 1,000 mm boom extension, a 130 HP Cummins engine and 5,000 kg operating weight.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 AFTER-SALES TECHNICAL SUPPORT

QINGDAO KONO DEERE MACHINERY CO.,LTD

info@kono-deere.com | WhatsApp +86 186 6143 3121

KD4200C

Configuration from the manufacturer-supplied specification. Final order confirmation applies.

GRAPPLE & REACH

Rated load	**800 kg**
Telescopic boom extension	**1,000 mm**
Maximum dumping height	**3,800 mm**
Maximum grapple height	**3,800 mm**
Maximum grapple opening	**1,200 mm**

ENGINE & POWER

Engine - configuration shown	**Cummins**
Rated engine power	**130 HP**
Maximum travel speed	**20 km/h**

DIMENSIONS & WEIGHT

Operating weight	**5,000 kg**
Overall dimensions (L × W × H)	**6,300 × 2,850 × 2,850 mm**
Minimum ground clearance	**550 mm**

CHASSIS & TIRES

Minimum turning radius	**3,300 mm**
Tire spacing	**2,150 mm**
Wheelbase	**3,300 mm**
Front tire size	**18.4-30**
Rear tire size	**400/60-15.5**

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations, subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.

QINGDAO KONO DEERE MACHINERY CO.,LTD

info@kono-deere.com | WhatsApp +86 186 6143 3121