FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD60

Excavator

Representative product image. Attachments shown may be optional.

5,500 kg	36.2 kW	3.8 m
WORKING WEIGHT	RATED ENGINE POWER	MAXIMUM DIGGING DEPTH

KD60 compact excavator with 5,500 kg working weight, 36.2 kW (48.3 HP) rated power and 3,800 mm maximum digging depth.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 TECHNICAL SUPPORT

QINGDAO KONO DEERE MACHINERY CO.,LTD
info@kono-deere.com | WhatsApp +86 186 6143 3121

KD60 / Excavator

CAPACITY AND DIGGING FORCE

Bucket capacity	**0.18-0.21 m³**
Working weight	**5,500 kg**
Bucket digging force	**4.1 ton-force**
Arm digging force	**2.5 ton-force**

POWER AND TRAVEL

Rated power	**36.2 kW (48.3 HP)**
Travel speed (two ranges)	**4.3 / 2.4 km/h**
Swing torque	**982 kgf·m**

WORKING RANGE

Maximum digging height	**5,795 mm**
Maximum dumping height	**4,110 mm**
Maximum digging depth	**3,800 mm**
Maximum vertical digging depth	**3,125 mm**
Maximum digging radius	**6,135 mm**

DIMENSIONS

Overall length	**5,850 mm**
Overall width	**1,860 mm**
Height to boom top	**1,930 mm**
Height to cab top	**2,590 mm**

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations are available subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.