

FOCUSED EQUIPMENT. PERSONAL SUPPORT.

KD930

Wheel Loader



Representative product image. Attachments shown may be optional.

1,600 kg

RATED LOAD

65 kW

RATED ENGINE POWER

1.0 m³

BUCKET CAPACITY

KD930 — Wheel Loader. 1,600 kg · 65 kW · 1 m³.

20 YEARS OF MANUFACTURING EXPERIENCE

24/7 TECHNICAL SUPPORT

KD930 / Wheel Loader**CAPACITY & DIMENSIONS**

Bucket capacity	1.0 m ³
Rated load	1,600 kg
Maximum dumping height	3,250 mm
Machine weight	4,700 kg
Bucket width	2,000 mm
Overall dimensions (L × W × H)	5,950 × 2,070 × 2,850 mm

ENGINE

Rated engine power	65 kW
Engine - configuration shown	YUNNEI
Engine model	YN4100ZY

CHASSIS & CONTROLS

Axle	Medium wheel-side reduction axle
Torque converter	280F
Boom thickness	30 mm
Control	J pilot control (single-lever operation)
Tire size	16/70-20
Gradeability	30%

Engine options: Cummins; EU Stage V or US EPA Tier 4 configurations are available subject to model compatibility and final order confirmation.

Specification notice: Product specifications and configurations can be customized to meet customer requirements, subject to final order confirmation. All technical specifications are subject to change without prior notice due to technical improvements and enhancements to manufacturing processes. The final technical specifications confirmed in the order shall prevail.